



www.aputure.com

sales@aputure.com

Aputure 120t

Lightstorm COB



Special Features

- TLCI ≥ 97 , High Color Restoration
- Dual Power Supply
- Dual Cooling Mode, One Key Switching
- Ultra Silent Fan, Noise Low to 18dB
- Standard Industrial Bowens Mount, Easy to Work With



<https://vimeo.com/aputure>



<https://twitter.com/aputurephoto>



<https://www.facebook.com/Aputure>



<https://www.youtube.com/user/aputurephoto>

Specifications

Operation Current	9A	Power Consumption	135W maximum
Power Supply	DC 15V	Cooling Mode	Active Cooling
TLCI	≥97	CQS	≥95
CRI	≥97	Color Temperature	3000K
Radio Frequency	2.4GHz	Channels	1/2/3
Groups	A/B/C/D	Remote Ability	≤100m
Sizes (L*W*H)	Light	336.4*186.3*283.9mm	
	Controller box Anton Bauer Battery	269.0*118.7*48.1mm(*vertical antennas included)	
	Controller box (V-Mount)	269.0*118.7*59.6mm(*vertical antennas included)	

Brightness (average)

Distance	0.5m	1m	2m
Footcandles	1032	232	57
LUX	11100	2500	610